



**Système Huntingdon Inc.**  
110 Wellington, Huntingdon (Québec) Canada J0S 1H0  
Tél.: 450 264-6146 Tél.: 1 800 363-5304 Fax: 450 264-6066  
info@systemeinc.com www.systemeinc.com

**FOLIA™ High Pressure Laminate-Faced Wall Modules**

## **Architect's and Designer's Specification Manual**

### **What is the Folia™ High Pressure Laminate-Faced Wall Modules?**

Folia™ panels are constructed of 1/16 » HPL laminate sheets adhered to a recycled cardboard honeycomb core within an aluminum perimeter frame, creating a lightweight modular wall system suitable for interior applications.

The FOLIA™ process of fusing digital output into high pressure laminate allows the incorporation of your custom graphics or brand image in an architectural product suitable for many uses.

Our in-depth research and development of the process permits us to reproduce custom images illustrations to photographic images, with a color fidelity and resolution never before seen in the graphic industry.

#### **Typical uses:**

- Trade Show Displays
- Commercial Product Displays
- Traveling Exhibits

#### **Why Specify Folia™ High Pressure Laminate-Faced Wall Modules?**

- 35 years of experience in an industry we founded
- 12-color high-definition printing standard, no additional charge
- High-strength with low weight
- Durable custom laminate surfaces with high-strength aluminum perimeter frame and connector extrusions
- Six quality inspection routines performed during our manufacturing process
- Custom constructed, padded crates provided for each shipment
- Limited 10-year warranty
- Conforms or exceeds NEMA industry standards
- Qualifies for LEED project points
- Most technically advanced Color Lab in the digital graphics industry
- Pre-Flight Department ensures complete accuracy of your graphic files
- Personal Service: Specific Project Manager assigned for the length of each project
- Technical support available to you at all times (for suggestions, advice and assistance with our Design Guidelines)
- In-house design department available to create visuals to meet your needs



**Système Huntingdon Inc.**  
 110 Wellington, Huntingdon (Québec) Canada J0S 1H0  
 Tél.: 450 264-6146 Tél.:1 800 363-5304 Fax: 450 264-6066  
 info@systemeinc.com www.systemeinc.com

**How to Specify & Order**

<b>1. Specify Size(s) of Panel</b>	<b>Quantity</b>
96" x 18"	_____
96" x 24"	_____
96" x 36"	_____
96" x 48"	_____
120" x 18"	_____
120" x 24"	_____
120" x 36"	_____
120" x 48"	_____
144" x 18"	_____
144" x 24"	_____
144" x 36"	_____
144" x 48"	_____

\* Custom Sizes Available – Attach drawing and quantities

**2. Specify Thickness of Panel(s)**

q 1"      q 2"

**3. Holes**

Holes must be drilled prior to processing (Attach sketch showing size and location with measurements from edges and center-to-center of all holes)

**Folia™ High Pressure Laminate-Faced Wall Modules General Information**

**1. Proofing - Choose:**

**Paper Content Proofs**

- 11" x 17" paper proofs are the most economical way to verify layout content.
- Larger layouts are reduced to fit the 11" x 17" printable area.

**Full-Scale Paper Proofs**

- Allows verification of content and legibility at full size.

**Half-Scale Paper Proofs**

- More economical than the full-scale, half-scale proofs allow accurate content verification.
- Best for large layouts with text that would be unreadable when reduced to 17" x 11".

**PDF Paperless Proofs**

**2. Hardware**

- Attach drawing if your quote includes drilled holes to a structure not supplied by SH[i]:
- Provide measurements from edge of panel to center of all holes
- Specify hole diameter clearly on drawing (we recommend 1/16" larger than the diameter of the screw thread
- Indicate required mounting screw length by adding the thickness of the mounting structure to the thickness of your (GLASS) panel

**Maintenance**

Clean only with non-abrasive cleaners like Windex, water with mild soap, followed by a warm water rinse, and dry with a clean, soft cloth.

To remove graffiti, use "Disappear-Organic Graffiti, Adhesive and Paint Remover™" and, if shadows persist, use "Professional's Choice Shadow Max™". Rinse with warm water and dry with a clean, soft cloth.

Be careful to not damage the surface or its finish sheen by bearing down too hard or over-cleaning.

